

RAAH Safety Manual Lifting Slings

Our Manual Lifting Slings are used to aid for safer handling of pipes, ironwork and tubing sections. Also reduce unnecessary bending and lifting.

Cautions:

- The product should be used by competent person
- For manual handling only, must not be used as part of any rigging or mechanical lifting arrangement
- Improper use of product could result in injuries
- Always hold the handle with arm in straight holding position, not over your back or shoulders
- When lifting, keep your back as straight as you can and use the power of your legs to lift
- Do not attempt to carry more than you can comfortably manage
- Personnel with known back, hip and muscular or other similar physical disorders should refrain from manual lifting activities
- Always inspect and maintain the lifting sling, look out for any abrasions or cuts on the sling, check the stitching for any abrasions, check the handle bolted properly. If not in proper condition DO NOT USE
- Usually to be used in pairs when handling pipes, tubulars and ironworks. Do not exceed the combined WLL mentioned on the sling
- When 2 persons are carrying the load, communicate so that both will lift at the same time, so as to prevent one personnel carrying too much load.
- Ensure the lifting slings are placed on suitable positions to allow an equal and balanced lift
- If you are in doubt how to safely use the product, don't make assumptions, contact us for advice.

Our Manual Lifting Slings are used to aid for safer handling of pipes, ironwork

RSS-S100 – RAAH Safety Single Handle Lifting Sling



- Designed for one per operation and can be used in pairs
- Can be used by putting the eye in the cylindrical load and simply lift
- Place load in middle of sling, pass the handle through the eye forming a choke as shown in picture and can be lifted
- Extra lengths provided to allow double wrapping and choke
- Reduces the need for bending, safe manual lifting, helps to prevent pinch-point and crush-point injuries to hands and fingers
- Comes with single eye, handle, buckle for length adjustments and slings
- WLL = 75kgs

RSS-D100 – RAAH Safety Double Handle Lifting Sling



- Designed for one person or two person use
- Recommended to place load in middle of sling. Loop one of the handles fully round the load and back. This way the sling wraps around and is more secure on the load
- Another way – To place both handles on one side and other side have 'U' of the sling. Place the load in the centre portion. Pass the 2 handles over the U to form a choke. This can prevent rollage of carried load.
- Extra lengths provided to allow double wrapping and choke
- Reduces the need for bending, safe manual lifting, helps to prevent pinch-point and crush-point injuries to hands and fingers
- Comes with two handles, buckle for length adjustments and slings
- WLL = 100kgs

