

WHIP CHECKS / CABLE HOSE RESTRAINTS



If a hose fails at the fitting area, Raah Safety - Cable Restraints are designed to give limited protection from hose whipping. The Cable Restraint will work on hoses ranging in size from 1/2" I.D to 4" I.D. and only should be used on hoses with a maximum pressure of 200 PSI.

Raah Safety Singapore - Cable Hose Restraints also known as Whip Checks are stocked in Raah Safety Indonesia as well. We recommend whipchecks be used only on AIR HOSES carrying no more than 200 PSI. Any other use is at your own risk.

The force calculator will give you the forces created during a failure with fluid. To calculate the force on hoses with air or gases, double the fluid reading. Fluid-100%

Air-200 %

Raah Safety Singapore - Cable Hose Restraints - Hose to Hose

PART NUMBERS	CABLE SIZE	HOSE RANGE INSIDE DIAMETER	MAXIMUM PSI
WC-1	1/8" X 20"	.5" - 1.25"	200 PSI
WC-2	3/16" X 28"	1.25" - 1.75"	200 PSI
WC-3	1/4" X 38"	2" - 3.5"	200 PSI
WC-4	3/8" X 44"	4" - 5"	200 PSI

Being committed to collate the BEST in specialised and innovative Oilfield Safety Products for our clients worldwide - Raah International - Raah Safety Division offers clients multiple Hose Safety products including Raah Safety - Cable Hose Restraints , Raah Safety - whip socks and whip stops and hose chokers.