

NYLON HOSE CHOKER

The Raah Safety NYLON HOSE CHOKER has a specially designed choking action which allows the nylon to tighten down on the hose during a failure. Unlike the WHIP CHECK or the steel Hobble Clamp, the NYLON HOSE CHOKER will continue tightening down sometimes even choking off the air for a more controlled release.

Raah International - Raah Safety Singapore and Raah Safety Indonesia - supplies the Nylon Hose Chokers and other Hose Safety products like Whip Stops and Whip Socks, Cable Hose Chokers , Hose Restraints, Hose Hobbles and other innovative hose safety products.

Raah International - Raah Safety Singapore supply hose safety products like hose chokers, hose restraints and whip stops , whip socks through agents to Oman, Kuwait, Saudi Arabia, Egypt and worldwide.

The force calculator will give you the forces created during a failure with fluid.To calculate the force on hoses with air or gases, double the fluid reading.

Fluid-100%

Air-200 %

Part #	Breaking	Length:	Recommended For Use On The Following Hose Inside Diameters Using "Fluid"								
	Strength	Loop to Loop	1/4"	3/8"	1/2"	3/4"	1"	2"	3"	4"	6"
			Hose Maximum Internal Pressure PSI At Above Hose I.D.								
NC118	4000 lbs	18"	26,000	20,000	13,000	6,000	3,000	-	-	-	-
NC124	4000 lbs	24"	26,000	20,000	13,000	6,000	3,000	-	-	-	-
NC130	4000 lbs	30"	26,000	20,000	13,000	6,000	3,000	-	-	-	-
NC136	4000 lbs	36"	26,000	20,000	13,000	6,000	3,000	-	-	-	-
NC156	7000 lbs	36"	-	-	-	-	-	1,450	650	350	-
NC180	7000 lbs	36"	-	-	-	-	-	-	650	350	150
NC218	8000 lbs	18"	40,000	30,000	27,000	12,000	6,500	1,650	-	-	-
NC224	8000 lbs	24"	40,000	30,000	27,000	12,000	6,500	1,650	-	-	-
NC236	8000 lbs	36"	-	-	-	-	6,500	1,650	750	400	-
NC248	8000 lbs	48"	-	-	-	-	6,500	1,650	750	400	175
NC260	8000 lbs	60"	-	-	-	-	-	1,650	750	400	175
NC330	12000 lbs	24"	-	-	40,000	18,000	10,000	2,500	-	-	-

NC364	12000 lbs	48"	-	-	-	-	-	2,500	1,100	600	250
NC430	16000 lbs	24"	-	-	-	24,000	13,500	3,350	-	-	-
NC444	16000 lbs	36"	-	-	-	-	13,500	3,350	1,500	800	-
NC464	16000 lbs	56"	-	-	-	-	-	3,350	1,500	800	350

Part #	Breaking	Length:	Recommended For Use On The Following Hose Inside Diameters Using "Air"								
	Strength	Loop to Loop	1/4"	3/8"	1/2"	3/4"	1"	2"	3"	4"	6"
			Hose Maximum Internal Pressure PSI At Above Hose I.D.								
NC118	4000 lbs	18"	26,000	12,000	6,500	3,000	1,700	-	-	-	-
NC124	4000 lbs	24"	26,000	12,000	6,500	3,000	1,700	-	-	-	-
NC130	4000 lbs	30"	26,000	12,000	6,500	3,000	1,700	-	-	-	-
NC136	4000 lbs	36"	26,000	12,000	6,500	3,000	1,700	-	-	-	-
NC156	7000 lbs	36"	-	-	-	-	-	725	325	175	-
NC180	7000 lbs	36"	-	-	-	-	-	-	325	175	75
NC218	8000 lbs	18"	40,000	15,000	13,000	6,000	3,350	825	-	-	-
NC224	8000 lbs	24"	40,000	15,000	13,000	6,000	3,350	825	-	-	-
NC236	8000 lbs	36"	-	-	-	-	3,350	825	375	200	-
NC248	8000 lbs	48"	-	-	-	-	3,350	825	375	200	85
NC260	8000 lbs	60"	-	-	-	-	-	825	375	200	85
NC330	12000 lbs	24"	-	-	20,000	9,000	5,000	1,250	-	-	-
NC364	12000 lbs	48"	-	-	-	-	-	1,250	550	300	125
NC430	16000 lbs	24"	-	-	-	12,000	6,750	1,675	-	-	-
NC444	16000 lbs	36"	-	-	-	-	6,750	1,675	750	400	-
NC464	16000 lbs	56"	-	-	-	-	-	1,675	750	400	175